

MINIBOX 21 SE 2 - Specification

Item	Quantity	Description	Unit Price	Total Price
		<p>Dimensions H x W x D = 218 x 300 x 388 (see data sheet KD321)</p> <p>Made of hot-pressed glass fibre reinforced polyester (GRP) Two-part construction: horizontal or vertical installation possible Stackable design for space-saving storage and transport Hardly inflammable and self-extinguishing Colour RAL 7032 light grey UV-resistant Weight: approx. 3 kg Protection class IP44</p> <p>Standard Design <input type="checkbox"/> SE2 Standard without cutouts with 2 clasps and 2 hinges in stainless steel</p> <p>Optional Designs <input type="checkbox"/> SV4 4 clasps <input type="checkbox"/> DSL Double row of hinges with C-rail</p> <p>Window <input type="checkbox"/> FS Safety glass window</p> <p>arctic additional Insulation PU-foam, not stackable <input type="checkbox"/> arctic-GRP GRP-lining</p> <p>Explosion Protection <input type="checkbox"/> GO Anti-static design to avoid electrostatic charge accumulation to DIN EN IEC 600079-0</p> <p>Increased Protection class <input type="checkbox"/> IP 65</p> <p>Cutouts <input type="checkbox"/> Cutout for FLEXIPASS R <input type="checkbox"/> Cutout for FLEXIPASS T <input type="checkbox"/> Cutout for window <input type="checkbox"/> Special cutout</p> <p>Accessories <input type="checkbox"/> FLEXIPASS R Entry seal, EPDM-foam for piping, 40 mm thick <input type="checkbox"/> FLEXIPASS T Entry seal for transmitter, 20 mm thick <input type="checkbox"/> BT Support bracket (internal), stainless steel (anodized aluminium upon request) for transmitter installation, adjustable <input type="checkbox"/> BU Support with C-rail, stainless steel <input type="checkbox"/> BR Support bracket (external), stainless steel for MINIBOX-installation on pipe stand <input type="checkbox"/> RS 21 Mounting bracket for 2" pipe stand <input type="checkbox"/> MS 50-QS-M Mounting rail <input type="checkbox"/> Mounting support for transmitter or shut-off valve</p>		